

MODEL : ID-A33



Features:

- 2 satellite IF and 1 terrestrial TV inputs & outputs
- 2 satellite IF inputs selected by 13V、 18V
- output ports -input ports DC Pass
- SAT-IF-PATHs to the subscribers are active and supplied by the receiver
- Sheet metal housing with plastic holder
- Design good for indoor usage

Specifications

Specifications		Typical	QC Limit	Remark
Item				
Frequency Range		Terr.:47~862MHz SAT:950~2150MHz		
Inputs		2 SAT+1 Terr.		F connectors
Outputs		2 SAT+1 Terr.		F connectors
Gain	Terr.	16dB	16±1dB	
	SAT	18-24dB	17-25dB	
Return Loss	Terr.	10dB	8dB	
	SAT	12dB	10dB	
Stop band attenuation	Terr.	25dB	20dB	
	SAT	25dB	20dB	
Isolation	H/V	30dB	25dB	
	SAT/Terr.	30dB	25dB	
Max. output level Terr.		108dBuV		IMA3-60dB
Max. output level SAT		105dBuV		IMA3-35dB
SAT Output Voltage		V:13.5V H:17.8V		
Power Adapter		IN:100~240V OUT:18V 500mA		
Dimensions (L,W,H)		124×125×43		mm