

# TOP-TEN H2IRF+



## MAIN FEATURES

- Fully compliant with DVB-S&S2 digital TV reception standard
- HDTV/ SDTV/ MPEG-2&H.264/AVS decoding
- Support 480i/480p/576i/576p/1080i/1080p
- INPUT Frequency: 950-2150MHz
- Support EPG/OTA/BISS/iptv
- Scan modes include blind scan, manual scan, default scan, and NIT
- Support USB upgrade
- Support USB 2.0 PVR, MP3, AVI, DAT, MKV, MPEG, BMP, FLV, VOB, JPG Photo playback

## TECHNICAL SPECIFICATION

<b>Chipset and Memory:</b>	CPU model : ALI3510G Flash : 64 Mbt Ram : DDR2 512Mbit
<b>Power:</b>	Input : 110-240V 50/60Hz Maximum power consumption : <12W Standby power : < 1w
<b>Interface:</b>	LNB IN*1 HDMI*1 RCA*1 USB 2.0 Port*1 RF IN *1 (Optional) RF OUT *1 (Optional)
<b>Tuner</b>	Tuner IC: RT720 Compliant with : DVB-S&S2 Receiving Frequency : 950-2150MHz Input signal level : +10---80 RF loop out function
<b>Demodulation</b>	Demod IC: SOC Compliant with DVB-S&S2 Demodulation: DVB-S QPSK; DVB-S2 QPSK/8PSK/16APSK/32APSK; Integrates LDPC and BCH decoders
<b>Video Decoding</b>	MPEG2 MP@HL MPEG4 compliant support SP@L3 to ASP@L5 H.264 BP(with no ASO/FMO), MP&HP@L4.1 Aspect ratio: 4:3/16:9
<b>Audio Decoding</b>	MPEG-1/2 Layer I/II/III MPEG-2/4 LC-AAC, MPEG-4 HE-AAC@Level4
<b>UI</b>	